



TESCON® WS is a pure aluminium tape applied to joinery for wet seal connections between pro clima TESCON EXTONSEAL® and window and door joinery. It is compatible with all pro clima membranes, underlays & tapes. TESCON® WS allows for a windtight and watertight adhesive seal to the smooth surface of TESCON EXTONSEAL® substrate, forming weathertight window and door connections under all conditions.

- ✓ For use with silicone, polymer and polyurethane sealants*
- ✓ Weathertight & airtight connection
- ✓ Outstanding adhesion to TESCON EXTONSEAL®
- ✓ Long-term durability
- ✓ Tested and proven in Australia & New Zealand



09 06 2021



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





Technical Data

Carrier material:	pure aluminium
Adhesive:	acrylic adhesive
Release material:	polyethylene (PE)
Temperature resistance:	-40 °C to +130 °C
Installation temperature:	> -10 °C
Thickness:	0.05 mm
Width:	38 mm
Colour:	aluminium
Storage:	cool and dry

**silicone, polymer and polyurethane sealants suitable for adhesion to aluminium can be used with TESCON® WS*

IMPORTANT INFORMATION

- Any sealants including silicone, polymer, polyurethane or any other products suitable for adhesion to aluminium surfaces can be used with TESCON® WS
- Guaranteed adhesion to the polypropylene surface of TESCON EXTONSEAL®
- Fully tested within AS/NZS 4284 & E2/AS1 weather testing scenarios

PRODUCT DESCRIPTION

TESCON® WS is a pure aluminium tape for wet seal connections to pro clima TESCON EXTONSEAL® and forms an essential part of any weather resistive barrier (WRB) system using wet seals around windows and doors. Made from aluminium, it complies with adhesion compatibility with any sealant suitable for window and door joinery.

WEATHER EXPOSURE

This product is not designed for direct exposure to weather elements including UV, and should be applied just prior to the installation of window or door suites.

APPLICATION NOTES

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal.

Delivery Form

ID CODE	LENGTH	WIDTH	QTY
16849	30 m	38 mm	1



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au

